
PEAKUP POWER

DANDELION

Light, flexible, perfect

2nd Gen.

PKQJH72I 555~565W



More hotspot resistance

based on our new PEC technology

More contact reliability

as there are no contact ribbons used, soldering stress is eliminated for reliable performance

More moisture barrier

as the more layers form a vapor barrier

More efficiency

as the cell conversion is up to 27% and performance been optimized by lower temperature

The next level of lightweight photovoltaic – addressing and solving challenges of people and companies which are in need for glass and lightweight photovoltaic by using our innovative PEC-BC technology – while keeping the weight low, ultra-thin, and flexible: just 2.5 kg/m², 2mm thin, with a minimum bending radius of 0.3m.

- Higher output - 2% more out of every module due to “miss” of busbars in the front of the cell and no shade created
- Higher reliability - as the lower degradation rate, superiority in fire-resistance, excellent performance in dynamic load (wind, snow, hail etc.) make them more durable and reliable
- Higher performance – due to optimized heat transmission using copper

CE

Type Tested

MPA STUTTGART Materialprüfungsanstalt Universität Stuttgart

For details regarding tests and certificates please refer to the rear page.

15 YEARS Product Warranty

25 YEARS Linear Performance Warranty

PEAKUP POWER

PKQJH721 555~565W


23.1%	0~3%	⩽2%	0.55%	BC HALF-CELL
MAX MODULE EFFICIENCY	POWER TOLERANCE	FIRST YEAR POWER DEGRADATION	YEAR 2-25 POWER DEGRADATION	Lower operating temperature

TYPICAL ELECTRICAL PARAMETERS

Model	PKQJH721555		PKQJH721560		PKQJH721565	
Testing Condition	STC	NOCT	STC	NOCT	STC	NOCT
Rated Power (Pmpp) /W	555	419	560	423	565	427
Rated Current (Impp) /A	12.59	10.08	12.67	10.15	12.75	10.21
Rated Voltage (Vmpp) / V	44.11	41.56	44.22	41.67	44.33	41.78
Short Circuit Current (Isc) /A	13.35	10.93	13.42	10.99	13.50	11.06
Open Circuit Voltage (Voc) /V	52.51	50.04	52.62	50.15	52.73	50.25
Effective Module Efficiency(η) /%	22.68%		22.89%		23.09%	

STC(Standard Testing Conditions): Irradiance 1000W/m², Air Mass 1.5, Cell Temperature 25℃, Measuring Tolerance ±3%

NOCT(Nominal Operating Cell Temperature): Irradiance 800W/m², Ambient Temperature 20℃, Air Mass 1.5, Wind speed 1m/s





ABSOLUTE MAXIMUM RATING

Operating Temperature	From -40 to +85℃
Maximum Series Fuse Rating	25A
Safety Class	II
Fire Rating (IEC 61730)	Class C
Maximum System Voltage	DC 1500V

MECHANICAL CHARACTERISTICS

Cell Type	Mono-crystalline BC, 144(12 x 12)
Effective Module Dimension(L×W)	2197.4×1113.5mm
Dimension (L×W×H)	2227x 1193x 2mm(87.4x47x0.07 inches)
Weight	6.6±0.5kg
Cable	4mm²(IEC), 450mm or customized length
Junction Box	IP68 with three bypass diodes
Connector	Original MC4





TEMPERATURE RATINGS

Voltage Temperature Coefficient	-0.220%/℃
Current Temperature Coefficient	+0.050%/℃
Power Temperature Coefficient	-0.240%/℃
Tolerance	0~+5W
NOCT	43 ± 2 ℃

PACKING CONFIGURATION

40'HQ Container	Pallet/container	Piece/container
Pieces (126 pcs per pallet)	16	2016

Test&classifications

- CE passed (according to low voltage directive (LVD) (2014/35/EU)
- Sand/dust: IEC 60068-2-68: 1994 modified
- Salt mist: IEC 61701:2020 / EN IEC 61701:2020
- Potential Induced Degradation (PID): IEC TS 62804-1:2015 modified
- Ammonia (NH_3): IEC 62716: 2013 / EN 62716: 2013
- Design qualification
  - IEC 61215-1:2021 / EN IEC 61215-1:2021;
  - IEC 61215-1-1:2021 / EN IEC 61215-1-1:2021;
  - IEC 61215-2:2021 / EN IEC 61215-2:2021;
- Construction requirements&safety
  - IEC 61730-1:2023;
  - IEC 61730-2:2023.
- Classification of external fire exposure
  - Class E (acc. DIN EN 13 501-1 : 2019)
  - Broof (t1) (for roofing-pitches < 20°) (acc. DIN EN 13 501-5: 2016 using test data from external fire exposure to roofs)